



Precision Plumbing Products
"Specify with Confidence - Install with Pride"

LEAD FREE

**NICKEL PLATED
 FLUID HAMMER ARRESTORS**

www.pppinc.net



PART NO.	SIZE
SNP-500	1/2"
SNP-750	3/4"
SNP-1000	1"
SNP-1250	1"
SNP-1500	1"
SNP-2000	1"

No access panel required.

Consult Local Code.

PROJECT SUBMITTAL

Project: _____

Contractor: _____

Engineer: _____

Date Submitted: _____

Prepared By: _____

**Over 40 years of outstanding
 performance**

Water Hammer Arrestors (Nickel Plated)

Normal operating pressure 35 to 250 PSIG.
 Spike pressure not to exceed 400 PSIG.

Arrestor Construction:

Threaded Adapter:

Machined of C69300 ECO Lead Free Brass.
 Type L copper barrel, Polycarbonate Dow Calibre 2016
 MFR piston, Nitrile "O" rings, Brass or Copper Cap de-
 pending on size. All parts 100% Nickel Plated.

Application:

Sea water, Petroleum, Chemicals and Corrosive fluids.
 Available in NPT or BSP threads.
 Manufacturing lead time: 4-6 weeks.

Precision Plumbing Products

Division of JL Industries, Inc.



JL Industries, Inc.

802 SE 199th Avenue
 Portland, Oregon 97233

T (503) 256-4010
 F (503) 253-8165

www.pppinc.net

