



Precision Plumbing Products

"Specify with Confidence - Install with Pride"

OPTIONAL ADJUSTABLE TIMER MODELS

ADJUSTABLE TIMER - Model #'s

- TMR-1-115V-ADJ**
- TMR-1-24V-ADJ**
- TMR-1-220V-ADJ**

Match Timer Voltage to Solenoid Voltage

EXAMPLE OF FACTORY SETTING:

6 seconds "ON" time, 24 hours "OFF" time.



ON TIME:

Top switch to the right all others to the left.

OFF TIME:

8 and 16 to the right and all others to the left.

Run time

Run time is given in minutes. Therefore 0.1 switch represents one tenth of a minute, or 6 seconds. The 0.2 switch represents two tenths of a minute or 12 seconds. The 6.4 switch represents 6 minutes and 24 seconds (.4 times 6 seconds equals 24 seconds). These switches are cumulative. All ON TIME switches set to the "ON" position must be added together to determine the total run time.

Off Time

"OFF" time is given in hours. Therefore "1" switch represents one hour. The "512" switch represents over 21 days. (512 hours divided by 24hrs/day). These switches are cumulative. All OFF TIME switches are cumulative.

The example above shows the standard factory setting of 6 seconds run time and 24 hrs. off time.



JL Industries, inc.

Precision Plumbing Products

Division of JL Industries, Inc.

802 SE 199th Ave
Portland, Oregon 97233

T (503) 256-4010
F (503) 253-8165

www.pppinc.net

