Precision Plumbing Products
802 S.E. 199th Avenue, Portland, Oregon, 97233 (503) 256-4010

INSTALLATION INSTRUCTIONS

TBX-3; 120 VAC & 24 VAC

DESCRIPTION:

The TBX-3 is an electronic timer box assembly. The timer can be utilized to control an electronic device to provide regular timed on-off cycles.

The TBX-3 assembly consists of:

1) Timer Box with test switch and circuit breaker
2) 3 butt connectors
3) Heat shrink tubing

OPERATION:

The timer is set-up to energize at regular intervals for a pre-determined length of time. The factory default cycle times are 10 seconds on and 24 hours off.

INSTALLATION:

1) The timer box must be installed in an accessible location.
   (1) For access panel doors where the timer is placed with an electronic trap priming valve (ie. Solo-Prime) use an 8” x 14” access panel door model D814PC prime coat or D814SS stainless steel.
   (2) For access panel doors where the timer is placed by itself use an 8” x 8” access panel door model D88PC prime coat or D88SS stainless steel.
2) Anchor timer control box to stud or surface wall.
3) Slide the supplied heat shrink tubing over the existing wires that you are connecting.
4) Make the wiring connection to the Pigtail wires using the crimp connectors.
5) Slide the section of heat shrink tubing over the butt connectors allowing the heat shrink tubing to overlap the insulation on the existing wire leads.
6) Apply heat to shrink tube taking care not to damage the wiring or insulation with excessive heat.
7) Make proper electrical connections for the 120VAC or 24VAC.
8) Function test the switch.
9) Check for proper function.

Statement of Warranty

Precision Plumbing Products of Portland, Oregon (USA) warrants our manufactured products to be free from defects and workmanship under normal use and service. The sole and exclusive remedy for our manufactured products that do not conform to this limited and express warranty and our sole obligation under this limited and express warranty is to replace the defective part or product during the three year period after original installation.

This warranty excludes any parts or products that are modified or improperly installed or installed where PH levels, chemical conditions or electrolysis prematurely degrade the product. We specifically disclaim any warranties or responsibility for defects due to quality, material, dimensional tolerances or quality control of any fitting or other third party supplied parts or components. **EXCLUSIONS OF ALL OTHER WARRANTIES INCLUDING IMPLIED WARRANTIES:** All other warranties, including the implied warranties of **MERCHANTABILITY** and fitness for a particular purpose, are **EXCLUDED** from this transaction and shall not apply to goods sold by us.

The above warranties are in lieu of all other warranties and representations, express or implied, and all other obligations or liabilities on our part. We shall not be liable for consequential damages, loss of profit, interruption of business or any other special, incidental, or punitive damages suffered or sustained by Customer. Any part or products being returned under this warranty must have prior authorization by us. Any part or product received by us without a return of goods authorization will be returned to the shipper.

All returned merchandise must be prepaid by shipper. Our personnel, including salespeople, as well as independent distributors and sales agents may have made oral statements about our products. Those statements are not warranties by us and should not be relied on by the buyer/customer/user. If you use this product you are agreeing to this warranty contract between us. This writing constitutes the final expression of the parties and is the complete and exclusive statement of that contract for warranties.

Precision Plumbing Products
Division of JL industries, inc.
Airport Business Center 802 SE 199th Avenue
Portland, Oregon 97218 (503) 256-4010 FAX: (503) 253-8165

Rev 05/09